

Damixa Silhouet, 1-handle kitchen mixer

Holder/Issued to

FM Mattsson Denmark ApS

Hvidkærvej 48, 5250 Odense SV, Denmark

Product description

Damixa Silhouet 1-handle kitchen mixer with cold start function. The swivel spout can be set to 120° or 360° and is available as a C- or J model. The mixers are equipped with an extra inlet and outlet for connection of e.g. separate filter. The mixers are supplied with flexible connection hoses covered by Swedish technical approval and has connection G3/8”.

Intended use

Kitchen mixer intended for drinking water.

Trade name

1-handle kitchen mixer Damixa Silhouet Instant, J-spout, article number 44900--.
1-handle kitchen mixer Damixa Silhouet Instant, C-spout, article number 44901--.

The 6th and 7th digit in the article No. describes the color:

00= chrome, 21= matt white, 46= steel, 55= brushed graphite grey, 61= matt black, 77= polished brass,
79= brushed brass, 87= brushed copper

Approval


The products satisfies the requirements set forth in chapter 8, 4 § 3 PBL, in respect to and under conditions stated in this type approval, and are therefore approved in accordance with the provisions of the following sections of Boverket Building Regulations (BBR):.

Tap water installations	6:62, 1st sentence and 2nd paragraph and general recommendation
Tap water flow	6:623, 1st sentence
Design	6:625, 1st and 4th paragraph

The provisions in Section 6:641 “Waste water installations” third paragraph of the Building Regulations (BBR) shall always be considered when installing.

Associated documents

Installation instruction 2029200 Rev.000 Silhouet Instant, version 2022-05-20.
User instruction 12676.00, version 2021-09.



Control

The factory production control (FPC) is monitored by an independent inspection body.
Control plan: Ref no. 210-17-0103, dated 2020-09-10, Inspection body: RISE.

When the building proprietor performs inspection at the building site, markings shall be checked to ensure that the correct products have been supplied and that they are used in accordance with the conditions in this type approval and associated documents. Further the product shall be accompanied by a manufacturer's assurance, certifying that the product has been manufactured in accordance with the documents on which this type approval is based.

Manufacturing places

Production control includes the following places:
FM Mattsson Denmark ApS Odense and production site 912350.

Marking

The products are to be marked at the factory. The marking consists of a text on every product and packing and includes:

Distributor*	Damixa
Product type designation	<i>see trade name</i>
Consecutive date of production*	<i>year.week</i>
Type approval number	C900714
Boverket's registered trade mark	†
RISE Accreditation number	1002
Certification body and Inspection body	RISE

*text on mixer

Basis for approval

Reports 1116318-A rev1, 178092-B rev1 and 1116318-B from RISE.
Reports Z-341449-21-Hy112, Z-337356-20-Hy220 and W-237426kk-13-SI from Hy.
Reports 5-018/22 and 5-0800A/21 from TZW.

Comments

Mixers are approved in accordance with EN 200 and EN 817.
Test according to NKB 4 is performed in triplicate to verify that migration of Nickel is <80 µg.

Classification of sound properties has been approved in accordance with EN ISO 3822.
Group 1: max 20dB (A) Lap at 0,3 MPa.
Group 2: max 30dB (A) Lap at 0,3 MPa.
Group 3: not classified.

The mixers are classified in group 1.

Associated documents shall accompany the product or by other means be available to users of the product.

Validity

Valid through 2027-09-29.

Validity of this type approval can be verified on our website.

The validity of this type approval expires when the type approved products with the intended use according to this type approval shall be CE-marked according to the Construction Products Regulation (EU) 305/2011.

A handwritten signature in blue ink, appearing to read 'Stefan Coric', is written over a light blue horizontal line.

Stefan Coric

This is a translation from the Swedish original document. In the event of any dispute as to its content, the Swedish text shall take precedence