

Pine, Solid, and Viskan single lever basin mixer

Holder/Issued to

FM Mattsson Denmark ApS

Hvidkærvej 48, 5250 Odense SV, Denmark

Product description

Damixa Pine and Solid single lever mixer, for washbasins with or without pop-up waste valve. The mixers have adjustable flow restrictor, temperature lock and cartridge with or without cold start. Mixers are supplied with flexible connection hoses that are covered by Swedish technical approval and have connection G3/8".

FM Mattsson Viskan single lever mixer, for washbasins with or without pop-up waste valve. The mixers have adjustable flow restrictor, temperature lock and cartridge with cold start. Mixers are supplied with flexible connection hoses that are covered by Swedish technical approval and have connection Ø 10 mm tube.

Intended use

Single lever mixer intended for hot and cold tap water.

Trade name

Damixa Pine with cold start, Damixa No 17021--00.

Damixa Pine, Damixa No 170211000.

Damixa Pine with cold start and pop up waste valve, Damixa No 17821--00.

Damixa Pine with cold start and pull rod waste valve, Damixa No 17822--00.

Damixa Pine high with cold start, Damixa No 17930--00.

Damixa Pine high with cold start and pull rod waste valve, Damixa No 17921--00.

Damixa Solid, Damixa no. 310210000

For Pine models the 6th and 7th digit position in the product No describes colour:
00 = chrome, 46 = steel, 61 = matt black

FM Mattsson Viskan washbasin mixer, FMM nr. 4950000-.

FM Mattsson Viskan washbasin mixer e med silpluggventil, FMM nr. 4953000-.

For Viskan models the 8th digit position in the product No describes colour:
0 = chrome, 4 = matt black

Approval

The products satisfy the requirements set forth in chapter 8, 4 § 3 PBL, in respect to and under conditions stated in this type approval, and are therefore approved in accordance with the provisions of the following sections of Boverket Building Regulations (BBR):

Tap water installations	6:62, 1 st sentence and 2nd paragraph and general recommendation
Tap water flow	6:623, 1st sentence
Design	6:625, 1st och 4th paragraph .

Associated documents

Installationsanvisning 20157.00 Damixa Pine, daterad 2022-06.
Installationsanvisning 20235.00 Solid, daterad 2020-08.
Installationsanvisning 20159.00 Kallstartsfunktion, daterad 2017-07.
Skötselanvisning 12676.00 Damixa, daterad 2021-09
Installationsanvisning LionX, Rev.003 -- 21.06.22 Mo nr 20197.00
Installationsanvisning Viskan, Rev.002 -- 21.06.21 -- FMM nr 20185.00

Control

The factory production control (FPC) is monitored by an independent inspection body.
Control plan: CR074, dated 2918-10-10, Inspection body: RISE

When the building proprietor performs inspection at the building site, markings shall be checked to ensure that the correct products have been supplied and that they are used in accordance with the conditions in this type approval and associated documents. Further the product shall be accompanied by a manufacturer's assurance, certifying that the product has been manufactured in accordance with the documents on which this type approval is based.

Manufacturing place

Production control includes the following places:
FM Mattsson Denmark ApS Odense and production site 912350.

Marking

The product/s is/are to be marked at the factory. The marking consists of a on every product supplied and includes:

Holder/Distributor	FM Mattsson Denmark ApS
Product type designation	Trade name
Date of production	no/date
Type approval number	SC0698-17
Boverket's registered trade mark	
RISE Accreditation number	1002
Inspection body	RISE

Basis for approval

Reports 178092-B, 178092-A, 7P04475E and 7P04475-01 from RISE.
Report 6P09796-05 from SP.
Rapport SBF2015F0290, 2017:00023 och 201700549A från SINTEF.
Report K-192852-10-Ko och W-233281-13-Si from Hy.
Report 57214216-1 from LGA.
Report DL-43580 from D-Lab.
Report 032100466-0001 from Kiwa.

Type Approval SC0698-17 | 2024-01-20

RISE Research Institutes of Sweden AB | Certification

Comments

Mixers are approved in accordance with SS-EN 817.

Classification of sound properties has been approved in accordance with EN ISO 3822.

Group 1: max 20dB (A) Lap at 0,3 MPa.

Group 2: max 30dB (A) Lap at 0,3 MPa.

Group 3: not classified.

The mixers are classified in group 1

Associated documents shall accompany the product or by other means be available to users of the product.

This type approval supersedes the previous type approval with the same number dated 2022-06-30.

Validity

Valid through 2027-06-29.

The validity of this type approval can be verified at RISE homepage.

The validity of this type approval expires when the type approved products with the intended use according to this type approval shall be CE-marked according to the Construction Products Regulation (EU) 305/2011.

A handwritten signature in blue ink, appearing to read 'Martin Tillander', with a long horizontal stroke extending to the right.

Martin Tillander

This is a translation from the Swedish original document. In the event of any dispute as to its content, the Swedish original shall take precedence.